

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number
WO 01/06238 A2

(51) International Patent Classification⁷: G01N 21/64,
G02B 21/00, G01N 33/58

Mack, J. [US/US]; 284 Lake Street, Belmont, MA 02478 (US). DOWD, Roger, D. [US/US]; 20 Franconia Avenue, Natick, MA 01760 (US). YANG, Jun [CN/CN]; 2315 14th Street, No. 7, Santa Monica, CA 90405 (US).

(21) International Application Number: PCT/US00/40276

(22) International Filing Date: 21 June 2000 (21.06.2000)

(74) Agents: SYROWIK, David, R. et al.; Brooks & Kushman, 22nd Floor, 1000 Town Center, Southfield, MI 48075 (US).

(25) Filing Language: English

(81) Designated States (*national*): CA, JP, US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(30) Priority Data:
09/354,500 16 July 1999 (16.07.1999) US

Published:

— Without international search report and to be republished upon receipt of that report.


(71) Applicant (*for all designated States except US*): GSI LUMONICS LIFE SCIENCE TRUST [CA/CA]; 105 Schneider Road, Kanata, Ontario K2K 1Y3 (CA).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): SCHERMER,

(54) Title: METHOD AND SYSTEM FOR AUTOMATICALLY CREATING CROSSTALK-CORRECTED DATA OF A MICROARRAY



(57) Abstract: A method and system are disclosed for automatically creating crosstalk-corrected data of a microarray utilizing calibration dye spots each of which comprises a single pure dye. A microarray scanner, such as a confocal laser microarray scanner, generates dye images, each of which contains at least one of the calibration dye spots for each of the output channels of the scanner. For each of the calibration dye spots, an output of each of the output channels is measured to obtain output measurements. A set of correction factors is computed from the output measurements to correct the data subsequently gathered from the microarray scanner. In other words, the correction factors are applied to quantitation or measurement data obtained from microarray images which contain spots having dyes of known or unknown excitation or emission spectra to obtain crosstalk-corrected data.

WO 01/06238 A2

METHOD AND SYSTEM FOR AUTOMATICALLY CREATING CROSSTALK-CORRECTED DATA OF A MICROARRAY

TECHNICAL FIELD

This invention relates to methods and systems for creating crosstalk-corrected data of a microarray and, in particular, to methods and systems for automatically creating crosstalk-corrected data of a microarray utilizing calibration spots.

BACKGROUND ART

Multifluorescence confocal imaging typically utilizes a multi-channel microarray scanner to obtain images of dye spots of a microarray. As illustrated in Figure 1, microarrays are created with fluorescently labeled DNA samples in a grid pattern consisting of rows 22 and columns 20 typically spread across a 1 by 3 inch glass microscope slide 24. Each spot 26 in the grid pattern 28 represents a separate DNA probe and constitutes a separate experiment. A plurality of such grid pattern comprises an array set 30. Reference or "target" DNA (or RNA) is spotted onto the glass slide 24 and chemically bonded to the surface. Fluorescently labeled "probe" DNA (or RNA) is introduced and allowed to hybridize with the target DNA. Excess probe DNA that does not bind is removed from the surface of the slide 24 in a subsequent washing process.

As illustrated in Figure 2, a confocal laser microarray scanner or microarray reader is commonly used to scan the microarray slide 24 to produce one image for each dye used by sequentially scanning the microarray with a laser of a proper wavelength for the particular dye. Each dye has a known excitation spectra as illustrated in Figure 3 and a known emission spectra as illustrated in Figure 4. The scanner includes a beam splitter 32 which reflects a laser beam 34 towards an objective lens 36 which, in turn, focuses the beam at the surface of slide 24 to cause fluorescent spherical emission. A portion of the emission travels back through the lens 36 and the beam splitter 32. After traveling through the beam splitter 32, the

fluorescence beam is reflected by a mirror 38, travels through an emission filter 40, a focusing detector lens 42 and a central pinhole 44. After traveling through the central pinhole 44, the fluorescence beam is detected by a detector, all in a conventional fashion.

5 The intent of a microarray experiment is to determine the concentrations of each DNA sample at each of the spot locations on the microarray. Further data analysis of the brightness values are typically done to produce a ratio of one dye's brightness to any or all of the other dyes on the microarray. An application of the microarray experiment is in gene expression experiments. Higher
10 brightness values are a function of higher concentrations of DNA. With a microarray, a researcher can determine the amount a gene is expressed under different environmental conditions.

 To be accurate, the reader must be able to quantitate the brightness of each microarray spot for each labeled DNA sample used in the experiment. To do
15 this the reader must filter the emissions from any and all other fluorescent samples. The concentration of the DNA is a function of the brightness of the emission when excited by a laser of the proper wavelength. It becomes difficult to differentiate between the emissions of different dyes when the emission spectra of a dye overlaps with another. Furthermore, the brightness produced from the emission of one dye
20 could be contaminated by emissions from another dye. This contamination of the brightness values is commonly known as crosstalk.

 Microarray readers have been designed to simultaneously scan more than two dyes using lasers with the proper wavelength. In this type of experiment, multiple samples of DNA are hybridized onto the microarray, each with a different
25 fluorescent label. Crosstalk contamination is equally likely as in the two dye experiments and can even be more troublesome when dyes with close emission spectra are placed on the same microarray.

 U.S. Patent Nos. 5,804,386 and 5,814,454 disclose sets of labeled energy transfer fluorescent primers and their use in multi-component analysis.

U.S. Patent No. 5,821,993 discloses a method and system for automatically calibrating a color camera in a machine vision system.

The paper by Schena, M., et al., (1995) "Quantitative Monitoring of Gene Expression Patterns With a Complementary DNA Microarray", Science 270; 467-469 is also related to the present invention.

DISCLOSURE OF INVENTION

An object of the present invention is to provide a method and system for creating crosstalk-corrected data of a microarray wherein a sequence of algebraic operations are used to obtain correction factors which, in turn, are used to correct for crosstalk between two or more dyes in a multi-channel imager such as a microarray scanner.

Another object of the present invention is to provide a method and system for creating crosstalk-corrected data of a microarray by utilizing calibration spots on a microarray sample substrate.

In carrying out the above objects and other objects of the present invention, a method is provided for automatically creating crosstalk-corrected data of a microarray. The method includes providing a microarray substrate having calibration dye spots. Each of the calibration dye spots comprises a single pure dye. The method also includes, for each of the calibration dye spots, generating a dye image containing at least one of the calibration dye spots for each of a plurality of output channels and also, for each of the calibration dye spots, measuring an output of each of the output channels to obtain output measurements. The method further includes computing a set of correction factors from the output measurements and applying the set of correction factors to data obtained from microarray images containing spots having dyes with excitation or emission spectra to obtain crosstalk-corrected data.

Preferably, the step of generating includes the step of imaging the calibration dye spots to produce a dye image for each calibration dye spot.

Preferably, the substrate is a glass slide.

Also, preferably, each of the channels is optimized for a different dye
5 and the step of generating is performed by an imager such as a microarray scanner or a camera.

Preferably, each of the dyes is a fluorescent dye.

Preferably, the step of computing includes the step of computing crosstalk ratios based on spot brightness values for each of the calibration dye spots
10 on each of the output channels.

Preferably, the number of calibration dye spots is more than or equal to the number of dyes.

The calibration dye spots may be hybridized target DNA and fluorescently labeled probe DNA.

15 Still further in carrying out the above objects and other objects of the present invention, a system is provided for carrying out the above method steps.

In the method and system of the present invention, crosstalk correction requires the availability and use of calibration spots on the microarray. As illustrated in Figure 5, these calibration spots should be composed of the highest concentration
20 of each single probe or dye that could be obtained by the microarray process being utilized. By measuring the crosstalk between the calibration spots, one can obtain all of the information that is needed to correct for crosstalk in all spots of the microarray without explicit knowledge of the dyes' excitation or emission characteristics.

In the case of 'n' samples on the microarray experiment with each DNA sample labeled (*i.e.*, typically 1000-5000 spots but only 2-4 dyes), the number of crosstalk calibration spots is typically greater than or equal to the number of dyes used. More calibration spots can be used to better tolerate experimental abnormalities. In the case of additional calibration spots, all the spots of an identical dye can be averaged together. The dyes used to create the calibration spots should also be the same as were used to label the DNA samples as illustrated in Figure 6.

The above objects and other objects, features and advantages of the present invention are readily apparent from the following detailed description of the best mode for carrying out the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIGURE 1 is a top plan schematic view illustrating a spot, an array and an array set on a glass slide;

FIGURE 2 is a schematic view of a confocal laser reader used to generate digital images;

FIGURE 3 illustrates graphs of sample excitation spectra;

FIGURE 4 illustrates graphs of sample emission spectra;

FIGURE 5 is a schematic view of calibration spots with two dyes;

FIGURE 6 is a schematic view of calibration spots with 'n' dyes;

FIGURE 7 is a schematic diagram illustrating a preferred hardware configuration on which the computational portion of the method of the present invention can be implemented; and

FIGURE 8 is a schematic view of a system in which the present invention can be utilized.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring now to the drawing figures, there is illustrated in Figure 7
5 a workstation on which the computational portion of the method and system of the present invention can be implemented. However, other configurations are possible. The hardware illustrated in Figure 7 includes a monitor 10 such as a single SVGA display, a keyboard 12, a pointing device such as a mouse 14, a magnetic storage device 16, and a chassis 18 including a CPU and random access memory. The
10 monitor 10 may be a touch screen monitor used in addition to standard keyboard/mouse interaction. In a preferred embodiment, the chassis 18 is a Pentium-based IBM compatible PC or other PC having at least 32 megabytes of RAM and at least 12 megabytes of hard disk space. The workstation typically includes a
15 Windows NT, graphical user interface as well as an Ethernet 10 Base-T high speed Lan network interface.

One or more images are obtained by a user from the microarray reader or scanner of Figures 2 and 8. The scanner is controlled by a scanner control computer 50 which, in turn, is also networked to a quantitation computer 52.

Calibration in the two channel microarray experiment

20 Assume that the user has provided two microarray spots for calibration as illustrated in Figure 5. Further assume two-color, two-channel scanning, with the microarray reader's channels balanced on these two calibration spots. The two dyes are called "Dye A" and "Dye B," and the instrument channels are called "Channel 1" and "Channel 2." Channel 1 is optimized for Dye A, and Channel 2 is optimized
25 for Dye B. These calibration spots should contain "pure" dye, or more precisely, the maximum labeled-DNA concentration associated with 100% gene expression.

These calibration spots are referred to as Cal Spot A and Cal Spot B. Before scanning them, the channels of the reader are balanced to produce roughly equivalent brightness values on a spot other than a Cal Spot. Crosstalk is a relatively small (2-5%) signal in the opposite channel. The two dots are scanned, both dots on both channels, and the scan data analyzed to produce spot brightness values. The four resulting data values are named as follows:

CalBrightA1 = spot brightness value of Cal Spot A scanned on Channel 1
CalBrightA2 = spot brightness value of Cal Spot A scanned on Channel 2
CalBrightB1 = spot brightness value of Cal Spot B scanned on Channel 1
CalBrightB2 = spot brightness value of Cal Spot B scanned on Channel 2

Crosstalk ratios are defined as follows:

Crosstalk A = $\text{CalBrightA2} / \text{CalBrightA1}$
Crosstalk B = $\text{CalBrightB1} / \text{CalBright B2}$

These two measured Crosstalk values (which are each a fraction less than 1) are stored for use in correcting values on all of the other dots on the array.

Correction in the two channel microarray experiment

The other dots in the array have random combinations of Dye A and Dye B in unknown ratios. Each dot is scanned on both Channel 1 and Channel 2, and those two raw brightness values are corrected for crosstalk. The first-order method for doing that is as follows.

Define more terms: "Brightness" is the measured intensity value for a spot from a particular instrument channel. "Signal" (1 and 2) is the portion of brightness (presumably the large majority) which is from the target dye (e.g., not crosstalk). "Signal" (1 and 2) is the answer that is sought.

Unknowns: Signal 1 = S_1

Signal 2 = S_2

Knowns: What is measured on each spot

Brightness 1 = B_1

Brightness 2 = B_2

5 From the two channel calibration section

Crosstalk₁₂ = α_{12}

Crosstalk₂₁ = α_{21}

Signal n for each spot on the array can then be determined by the following equations:

10 $B_1 = S_1 + S_2\alpha_{12}$

$B_2 = S_2 + S_1\alpha_{21}$

or, solving for Signal:

$S_1 = (B_1 - (\alpha_{12} \times B_2)) / (1 - (\alpha_{12} \times \alpha_{21}))$

$S_2 = (B_2 - (\alpha_{21} \times B_1)) / (1 - (\alpha_{12} \times \alpha_{21}))$

15 Calibration and correction in the 'n' channel microarray experiment

Scanners with 3, 4, or more channels are perhaps even more likely to suffer from crosstalk than 2-channel instruments. Correction for this is accomplished using the same calibration spot technique, and the measurement of the crosstalk contribution of all of the combinations of excitation wavelengths and dyes.

20 To generalize some definitions of terms:

α_{xy} = measured and calculated crosstalk ratio of Dye Y into the Dye X channel

S_x = Signal from Dye X (which one is seeking)

25 B_x = Measured brightness of an arbitrary spot on the Dye X channel

Then, for the 3-channel case, the equations are as follows:

$$B_1 = S_1 + S_2\alpha_{12} + S_3\alpha_{13}$$

$$B_2 = S_1\alpha_{21} + S_2 + S_3\alpha_{23}$$

$$B_3 = S_1\alpha_{31} + S_2\alpha_{32} + S_3$$

5 which, in matrix form looks like:

$$[B_x] = [S_x][A] \text{ where } A = \begin{bmatrix} 1 & \alpha_{12} & \alpha_{13} \\ \alpha_{21} & 1 & \alpha_{23} \\ \alpha_{31} & \alpha_{32} & 1 \end{bmatrix}$$

$$\text{DET } A = 1 - \alpha_{12}\alpha_{21} - \alpha_{13}\alpha_{31} - \alpha_{23}\alpha_{32} + \alpha_{13}\alpha_{21}\alpha_{32} + \alpha_{12}\alpha_{23}\alpha_{31}$$

$$S_1 = \frac{B_1(1 - \alpha_{23}\alpha_{32}) - B_2(\alpha_{12} - \alpha_{13}\alpha_{32}) + B_3(\alpha_{12}\alpha_{23} - \alpha_{13})}{\text{DET } A}$$

$$S_2 = \frac{-B_1(\alpha_{21} - \alpha_{31}\alpha_{23}) + B_2(1 - \alpha_{31}\alpha_{13}) - B_3(\alpha_{23} - \alpha_{21}\alpha_{13})}{\text{DET } A}$$

$$10 \quad S_3 = \frac{B_1(\alpha_{21}\alpha_{32} - \alpha_{31}) - B_2(\alpha_{32} - \alpha_{12}\alpha_{31}) + B_3(1 - \alpha_{12}\alpha_{21})}{\text{DET } A}$$

The expansion of this matrix from 3 x 3 to 4 x 4 (or n x n) is straightforward.

15 While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A method for automatically creating crosstalk-corrected data of a microarray, the method comprising:
 - providing a microarray substrate having calibration dye spots, each of the calibration dye spots comprising a single pure dye;
 - for each of the calibration dye spots, generating a dye image containing at least one of the calibration dye spots for each of a plurality of output channels;
 - for each of the calibration dye spots, measuring an output of each of the output channels to obtain output measurements;
 - computing a set of correction factors from the output measurements;
 - and
 - applying the set of correction factors to data obtained from microarray images containing spots having dyes with excitation or emission spectra to obtain crosstalk-corrected data.
2. The method as claimed in claim 1 wherein the step of generating includes the step of imaging the calibration dye spots to produce a dye image for each calibration dye spot.
3. The method as claimed in claim 1 wherein the substrate is a glass slide.
4. The method as claimed in claim 1 wherein each of the channels is optimized for a different dye.
5. The method as claimed in claim 1 wherein the step of generating is performed by an imager.
6. The method as claimed in claim 1 wherein each of the dyes is a fluorescent dye.

7. The method as claimed in claim 1 wherein the step of computing includes the step of computing crosstalk ratios based on spot brightness values for each of the calibration dye spots on each of the output channels.

8. The method as claimed in claim 1 wherein the number of calibration dye spots is more than or equal to the number of dyes.

9. The method as claimed in claim 1 wherein the calibration dye spots are hybridized target DNA and fluorescently labeled probe DNA.

10. A system for automatically creating crosstalk-corrected data of a microarray, the system comprising:

10 a microarray substrate having calibration dye spots, each of the calibration dye spots comprising a single pure dye;

an imager having a plurality of output channels wherein for each of the calibration dye spots the imager generates a dye image containing at least one of the calibration dye spots for each of the output channels;

15 means for measuring an output of each of the output channels for each of the calibration dye spots to obtain output measurements;

means for computing a set of correction factors from the output measurements; and

means for applying the set of correction factors to data obtained from microarray images containing spots having dyes with excitation or emission spectra to obtain crosstalk-corrected data.

11. The system as claimed in claim 10 wherein the imager is a microarray scanner which produces a dye image for each calibration dye spot by scanning the microarray substrate with a laser of a proper wavelength for the particular dye.

12. The system as claimed in claim 10 wherein the substrate is a glass slide.

13. The system as claimed in claim 10 wherein each of the channels is optimized for a different dye.

14. The system as claimed in claim 11 wherein the microarray scanner is a confocal laser microarray scanner.



5 15. The system as claimed in claim 10 wherein each of the dyes is a fluorescent dye.

16. The system as claimed in claim 10 wherein the means for computing includes means for computing crosstalk ratios based on spot brightness values for each of the calibration dye spots on each of the output channels.

10 17. The system as claimed in claim 10 wherein the number of calibration dye spots is more than or equal to the number of dyes.

18. The system as claimed in claim 10 wherein the calibration dye spots are hybridized target DNA and fluorescently labeled probe DNA.

1/3

*Fig. 1**Fig. 2*




Fig. 3




Fig. 4




Fig. 5




Fig. 6

3/3





Fig. 8



(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number
WO 01/06238 A3

(51) International Patent Classification⁷: **G01N 21/64,**
G02B 21/00, G01N 33/58

Natick, MA 01760 (US). YANG, Jun [CN/CN]; 2315 14th
Street, No. 7, Santa Monica, CA 90405 (US).

(21) International Application Number: PCT/US00/40276

(74) Agents: SYROWIK, David, R. et al.; Brooks & Kushman,
22nd Floor, 1000 Town Center, Southfield, MI 48075 (US).

(22) International Filing Date: 21 June 2000 (21.06.2000)

(81) Designated States (*national*): CA, JP, US.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).

(26) Publication Language: English

(30) Priority Data:
09/354,500 16 July 1999 (16.07.1999) US

Published:

- With international search report.
- Before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments.

(71) Applicant (*for all designated States except US*): GSI
LUMONICS LIFE SCIENCE TRUST [CA/CA]; 105
Schneider Road, Kanata, Ontario K2K 1Y3 (CA).


(88) Date of publication of the international search report:
22 March 2001

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): SCHERMER,
Mack, J. [US/US]; 284 Lake Street, Belmont, MA 02478
(US). DOWD, Roger, D. [US/US]; 20 Franconia Avenue.

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: METHOD AND SYSTEM FOR AUTOMATICALLY CREATING CROSSTALK-CORRECTED DATA OF A
MICROARRAY



(57) Abstract: A method and system are disclosed for automatically creating crosstalk-corrected data of a microarray utilizing calibration dye spots each of which comprises a single pure dye. A microarray scanner, such as a confocal laser microarray scanner, generates dye images, each of which contains at least one of the calibration dye spots for each of the output channels of the scanner. For each of the calibration dye spots, an output of each of the output channels is measured to obtain output measurements. A set of correction factors is computed from the output measurements to correct the data subsequently gathered from the microarray scanner. In other words, the correction factors are applied to quantitation or measurement data obtained from microarray images which contain spots having dyes of known or unknown excitation or emission spectra to obtain crosstalk-corrected data.

WO 01/06238 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/40276

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01N21/64 G02B21/00 G01N33/58

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01B G01N G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 578 832 A (FODOR STEPHEN P A ET AL) 26 November 1996 (1996-11-26) column 4-5; figures 1,3,11,12,15,18-20 column 22-25	1-18
X	US 5 807 522 A (BROWN PATRICK O ET AL) 15 September 1998 (1998-09-15) column 1-2; figures 3,4 column 16-17	1-18
A	US 5 814 454 A (JU JINGYUE) 29 September 1998 (1998-09-29) column 4-5 column 8, line 65 -column 9, line 35 -/--	1-18

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *8* document member of the same patent family

Date of the actual completion of the international search

4 January 2001

Date of mailing of the international search report

19/01/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mason, W

INTERNATIONAL SEARCH REPORT

Inter- national Application No
PCT/US 00/40276

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 15649 A (CREMER THOMAS ;CRAIG JEFF (DE); UNIV HEIDELBERG (DE)) 16 April 1998 (1998-04-16) page 3 page 6-7 -----	1-18
A	WO 98 17992 A (APPLIED IMAGING INC ;GINESTET JACQUES (US)) 30 April 1998 (1998-04-30) page 11 -page 14 -----	1-18
A	US 5 702 887 A (FISCHER WALTER ET AL) 30 December 1997 (1997-12-30) column 35-39 -----	1-18
A	US 5 728 528 A (MATHIES RICHARD A ET AL) 17 March 1998 (1998-03-17) column 8 -----	1-18
A	US 5 853 992 A (MATHIES RICHARD A ET AL) 29 December 1998 (1998-12-29) column 14 -----	1-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/40276

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5578832 A	26-11-1996	US 5834758 A US 6025601 A	10-11-1998 15-02-2000
US 5807522 A	15-09-1998	AT 180570 T AU 709276 B AU 2862995 A CA 2192095 A DE 69509925 D DE 69509925 T DK 804731 T EP 0804731 A EP 0913485 A ES 2134481 T GR 3030430 T JP 10503841 T US 6110426 A WO 9535505 A	15-06-1999 26-08-1999 15-01-1996 28-12-1995 01-07-1999 09-12-1999 08-11-1999 05-11-1997 06-05-1999 01-10-1999 30-09-1999 07-04-1998 29-08-2000 28-12-1995
US 5814454 A	29-09-1998	US 5804386 A US 5952180 A AU 5602298 A EP 0943019 A WO 9831834 A	08-09-1998 14-09-1999 07-08-1998 22-09-1999 23-07-1998
WO 9815649 A	16-04-1998	AU 4116397 A EP 0951566 A	05-05-1998 27-10-1999
WO 9817992 A	30-04-1998	US 5880473 A AU 4920297 A	09-03-1999 15-05-1998
US 5702887 A	30-12-1997	US 5395752 A AU 677259 B AU 5501894 A CA 2118891 A EP 0617288 A JP 8320319 A PL 306210 A WO 9421823 A US 5879894 A	07-03-1995 17-04-1997 22-09-1994 20-09-1994 28-09-1994 03-12-1996 06-03-1995 29-09-1994 09-03-1999
US 5728528 A	17-03-1998	CA 2231475 A EP 0851867 A JP 3066984 B JP 10511987 T WO 9711084 A	27-03-1997 08-07-1998 17-07-2000 17-11-1998 27-03-1997
US 5853992 A	29-12-1998	AU 717018 B AU 4742397 A EP 0935670 A GB 2317951 A, B WO 9814612 A US 6150107 A	16-03-2000 24-04-1998 18-08-1999 08-04-1998 09-04-1998 21-11-2000